

Atty Do ket No. JCLA8739

Serial No. 10/065,206

**AMENDMENTS****In The Claims:**

**Claim 1. (currently amended)** A belt tension adjustment apparatus for providing a proper-tension in a transmission belt inside a station, wherein the station at least ~~includes~~ comprises a main body casing, a pair of belt wheels and a transmission system, the belt wheels, the transmission system and the transmission belt are all enclosed inside the main body casing, the transmission belt is wrapped around the belt wheels, the transmission system is coupled to one of the belt wheels, and the belt tension adjustment apparatus ~~includes~~ comprises a plate spring having a bow in the middle with ends gripping the transmission belt such that a section of the transmission belt forms a bend to provide a proper-tension in the belt.

**Claims 2-3. (cancelled)**

**Claim 4. (currently amended)** A belt tension adjustment apparatus for providing a tension in a transmission belt inside a station, wherein the station at least comprises a main body casing, a pair of belt wheels and a transmission system, the belt wheels, the transmission system and the transmission belt are all enclosed inside the main body casing, the transmission belt is wrapped around the belt wheels, the transmission system is coupled to one of the belt wheels, and the belt tension adjustment apparatus comprising:

a plate spring having a bow in the middle with ends gripping the transmission belt such that a section of the transmission belt forms a bend to provide a tension in the belt; and

Atty Docket No. JCLA8739

Serial No. 10/065,206

~~The belt tension adjustment apparatus of claim 1, wherein the apparatus further includes~~  
~~comprises~~ a tension spring whose ends are connected to the ends of the plate spring.

**Claim 5. (original)** The belt tension adjustment apparatus of claim 4, wherein the tension spring is a helical tension spring.

**Claim 6. (currently amended)** The belt tension adjustment apparatus of claim 4, wherein the plate spring further ~~includes~~ comprises a latching groove structure at each end of the plate spring and a latching hook at each end of the tension spring, and the latching hooks at the end of the tension spring are engaged to the latching groove structures at the end of the plate spring.

**Claim 7. (currently amended)** The belt tension adjustment apparatus of claim 1, wherein the transmission system further ~~includes~~ comprises an electric motor and a gearset, the motor couples with the gearset and the gearset is coupled to one of the belt wheels so that the motor is able to drive one of the belt wheels.

**Claim 8. (currently amended)** The belt tension adjustment apparatus of claim 1, wherein the transmission belt ~~includes~~ comprises a belt with internal teeth.

**Claim 9. (currently amended)** A belt tension adjustment apparatus for an optical scanner, wherein the optical scanner ~~includes~~ comprises at least a main body casing, a scanning module, a transmission system, a pair of belt wheels and a transmission belt, the main body

**Atty Docket No. JCLA8739****Serial No. 10/065,206**

casing has a transparent platform thereon, the scanning module is capable of reciprocating forward and backward inside the main body casing underneath the transparent platform to scan a document placed over the transparent platform, the transmission system, the transmission belt and the belt wheels are all enclosed ~~inside~~ comprise the main body casing, and the transmission system is coupled to one of the belt wheels for driving the transmission belt and hence moving the scanning module that attaches to the belt, comprising:

a plate spring having a bow in the middle with ends gripping the transmission belt so that a section of the transmission belt bends to provide a tension in the belt; and

a tension spring whose ends are engaged to the respective end of the plate spring.

**Claim 10. (original)** The belt tension adjustment apparatus of claim 9, wherein the plate spring deforms elastically between a first configuration with the plate spring fully opened and a second configuration with the plate spring fully closed, and the plate spring is in a third configuration intermediate between the first configuration and the second configuration when the plate spring is mounted on the transmission belt.

**Claim 11. (currently amended)** The belt tension adjustment apparatus of claim 9, wherein the plate spring further ~~includes~~ comprises a gripping structure at each end of the plate spring for gripping the transmission belt.

Atty Dock t No. JCLA8739

Serial No. 10/065,206

**Claim 12. (currently amended)** The belt tension adjustment apparatus of claim 9, wherein the plate spring further ~~includes~~ comprises a latching groove structure at each end of the plate spring and a latching hook at each end of the tension spring, and the latching hooks at the end of the tension spring are engaged to the latching groove structures at the end of the plate spring.

**Claim 13. (currently amended)** The belt tension adjustment apparatus of claim 9, wherein the transmission system further ~~includes~~ comprises an electric motor and a gearset, the motor couples with the gearset and the gearset is coupled to one of the belt wheels so that the motor is able to drive one of the belt wheels.

**Claim 14. (currently amended)** The belt tension adjustment apparatus of claim 9, wherein the transmission belt ~~includes~~ comprises a belt with internal teeth.

**Claim 15. (currently amended)** An optical scanner, comprising:

- a main body casing having a transparent platform thereon;
- a pair of belt wheels inside the main body casing;
- a transmission belt inside the main body casing and wrapped around the belt wheels;
- a scanning module capable of reciprocating forward and backward inside the main body casing underneath the transparent platform, wherein the scanning module is attached to the transmission belt and hence is driven by the belt;
- a transmission system inside the main body casing and coupled with one of the belt

Atty Docket No. JCLA8739

Serial No. 10/065,206

wheels for driving the belt wheel; and

a tension adjustment apparatus mounted on the transmission belt for adjusting tension in the belt, wherein the tension adjustment apparatus further comprises a tension spring whose ends engage with the respective end of the plate spring.

**Claim 16. (currently amended)** The optical scanner of claim 15, wherein the tension adjustment apparatus further ~~includes~~ comprises a plate spring having a bow in the middle with ends gripping the transmission belt so that a section of the belt bends to produce a tension in the belt.

**Claim 17. (cancelled)**

**Claim 18. (original)** The optical scanner of claim ~~17~~15, wherein the tension spring is a helical tension spring.

**Claim 19. (currently amended)** The optical scanner of claim 15, wherein the transmission system further ~~includes~~ comprises an electric motor and a gearset, the motor couples with the gearset and the gearset is coupled to one of the belt wheels so that the motor is able to drive one of the belt wheels.

**Claim 20. (currently amended)** The optical scanner of claim 15, wherein the transmission belt ~~includes~~ comprises a belt with internal teeth.

Atty Docket No. JCLA8739

S rial N . 10/065,206

**Claim 21. (new)** The belt tension adjustment apparatus of claim 4, wherein the transmission system further comprises an electric motor and a gearset, the motor couples with the gearset and the gearset is coupled to one of the belt wheels so that the motor is able to drive one of the belt wheels.

**Claim 22. (new)** The belt tension adjustment apparatus of claim 4, wherein the transmission belt comprises a belt with internal teeth.

**Claim 23. (new)** A belt tension adjustment apparatus for providing a tension in a transmission belt inside a station, wherein the station at least comprises a main body casing, a pair of belt wheels and a transmission system, the belt wheels, the transmission system and the transmission belt are all enclosed inside the main body casing, the transmission belt is wrapped around the belt wheels, the transmission system is coupled to one of the belt wheels, and the belt tension adjustment apparatus comprises a plate spring having a bow in the middle with ends gripping the transmission belt such that a section of the transmission belt forms a bend to provide a tension in the belt;

wherein the plate spring deforms elastically between a first configuration with the plate spring fully opened and a second configuration with the plate spring fully closed, and the plate spring is in a third configuration intermediate between the first configuration and the second configuration when the plate spring is mounted on the transmission belt.

Atty Dock t No. JCLA8739

Serial No. 10/065,206

**Claim 24. (new)** The belt tension adjustment apparatus of claim 23, wherein the transmission system further comprises an electric motor and a gearset, the motor couples with the gearset and the gearset is coupled to one of the belt wheels so that the motor is able to drive one of the belt wheels.

**Claim 25. (new)** The belt tension adjustment apparatus of claim 23, wherein the transmission belt comprises a belt with internal teeth.

**Claim 26. (new)** A belt tension adjustment apparatus for providing a tension in a transmission belt inside a station, wherein the station at least comprises a main body casing, a pair of belt wheels and a transmission system, the belt wheels, the transmission system and the transmission belt are all enclosed inside the main body casing, the transmission belt is wrapped around the belt wheels, the transmission system is coupled to one of the belt wheels, and the belt tension adjustment apparatus comprises a plate spring having a bow in the middle with ends gripping the transmission belt such that a section of the transmission belt forms a bend to provide a tension in the belt;

wherein the plate spring further comprises a gripping structure at each end of the plate spring for gripping the transmission belt.

**Claim 27. (new)** The belt tension adjustment apparatus of claim 26, wherein the transmission system further comprises an electric motor and a gearset, the motor couples with the

Atty Dock t No. JCLA8739

Serial N . 10/065,206

gearset and the gearset is coupled to one of the belt wheels so that the motor is able to drive one of the belt wheels.

**Claim 28. (new)** The belt tension adjustment apparatus of claim 26, wherein the transmission belt comprises a belt with internal teeth.